

## Datasheet: VR2440 Range

### 24V AC 4A Low Profile PSU Range

Part Number	Description
VR2440	24V ac 4A (1 x 4A output)
VR2440-4	24V ac 4A (4 x 1A output)
VR2440-8	24V ac 4A (8 x 500mA output)

#### Overview:

A range of power supply units providing 24V ac @ 4A, ideal for CCTV applications.

They feature a single 24V ac transformer design, continuously supplying full rated current to load, with single or multiple outputs. Mains input voltage is 230V ac (nominal).

Input	
Voltage	230V ac (+10% / -15%)
Frequency	50Hz
Max Current	520mA
Mains Input Fuse	T2.0A HRC

Output	
Voltage	23V – 28V ac (24V ac nominal) Full load to off load @ 230V ac
Maximum Load Current	4A
Output Fuse(s)	1 x F4.0A – VR2440 4 x F1.0A – VR2440-4 8 x F500mA – VR2440-8

Local Indicators	
Mains LED (Green)	No
Fault LED (Red)	No

Mechanical	
Dimensions (mm)	185H x 200W x 55D
Weight	1.6Kg
Material	1.2mm Powder Coated Mild Steel
Colour	White

Environmental	
Environmental Rating	Indoor use only
Operating Temperature	0°C to +40°C 75% RH Non Condensing
Storage Temperature	-20°C to +50°C

Compliance	
CE Approved	Yes
RoHS Compliant	Yes

